LCD TV Product Specification

KTC Model Name: 43D1S Base Model: BCCE-43A Customer Model Name:

Platform Model: M-9216M3C1-ISDB-A Brand:

Figure(This is for your reference only)



1.Panel spec (The panel parameters will be somewhat different between different OC, ple	ease refer to
the corresponding panel specification.)	

Size	42.51" diagonal
Backlight	DLED direct Type
Maximum resolution	1920×1080
Contrast ratio (Typ)	1200:1
Response time(Typ)	8ms
Display scale	16:09
Viewing angle(CR>10)	Typ(H:178°, V:178°)
Display Colors	16. 7 M
Color Gamut(NTSC)	≥NTSC 62%
LCM Center Luminance of White	Min: 220cd/m2; Typ: 260cd/m2
Local dimming	Nonsupport
Uniformity of Luminance	≥65%

2.Hardware Information

ATV	PAL M/N; NTSC M
DTV	ISDB
CPU Frame	ARM Cortex-A55/1.45GHz/Quad core
GPU	Mali G31 MP2/Dual-core
RAM(DDR3)	1GB
ROM(Flash)	8GB
Audio power(Output)	8W+8W
WIFI(Type)	2R2T
HDMI 1.4 (HDCP 1.4)	_
HDMI 2.0 (HDCP 2.2)	2
USB 2.0	2
USB 3.0	_
VGA	_
AV In	1
YPbPr In	_
CI	_

PC Audio	-	
RJ-45	1	
Earphone	-	
Audio In	-	
Audio Out	-	
Video Out	-	
SPDIF Out	1	
Bluetooth(Version)	5. 1	
Tuner type	Screw head	
3.Software Function		
Channel list	YES	
Channel edit	YES	
Picture freezing	NO	
MTS/NICAM	YES	
Sleep time setting	YES	
Teletext	NO	
PVR	YES	
V_CHIP/Parental Guidance	Parental Guidance	
CC(Closed caption)	YES	
AD(Audio description)	YES	
CI+	NO	
DOLBY	YES	
HDMI-ARC	YES	
HDMI-CEC	YES	
HDMI-MHL	NO	
Operation system	Android11	
ОТА	YES	
Hotel mode	NO	
EPG	YES	
TTS(Text to Speech)	NO	
4.Structure Information		
Base model name	BCCE-43A Crescent plastic stand	
Size (without stand) L×W×H	969×73×566mm	
Size (with stand) L×W×H	969x235x618mm	
Size (carton) L×W×H	1080x119x652mm	
Net Weight (without stand)	6. 905kg	
Net Weight (with stand)	7kg	
Gross Weight (without stand)	8. 905kg	
Gross Weight (with stand)	9kg	
Size (Wall hanging)	400×200mm	

5.Power Management&Safety&Certificate		
Power input	100-240VAc	
Fire rating	UL94-HB75	
Standby power	≤0.5W	
Rated power	75W	
Working condition	Temperature: 5° C \sim 40 $^{\circ}$ C humidity: 20% \sim 80% atmosphere: 86KPa \sim 106KPa	
Storage condition	Temperature: -20°C~55°C humidity: 20%~80% atmosphere: 86kPa~106kPa	
6.Accessory		
Stand(Optional)	1PCS	
Remote control	1PCS	
Instruction	1PCS	
Warranty card(Optional)	-	
Battery(Optional)	2PCS	
Remark 1: The panel parameters will be somewhat different between different panel, please refer to the corresponding panel. Remark 2: This SPEC is confirmed by KTC and Customer, it will be effective from the dated signed. KTC will control the mass production according to this SPEC and in case all disputes arising from the execution of this agreemen, this SPEC should be prevail.		
Signed by PM:	Signed by sales Manager:	
Signed by customer:	Date:	